

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**




FIGURE 1




FIGURE 2




FIGURE 3

PROGRAM		VBL (V)	VWL (V)	PROGRAM	
	SC/SR	8	0	YES	401
	SC/UR	8	8	NO	403
	UC/SR	3.3	0	NO	405
	UC/UR	3.3	8	NO	407
				ISENSE	
READ	SC/SR	1.8	0	YES	409
	SC/UR	1.8	1.8	NO	411
	UC/SR	0	0	NO	413
	UC/UR	0	1.8	NO	415

FIGURE 4




FIGURE 5




FIGURE 6




FIGURE 7




FIGURE 8




FIGURE 9




FIGURE 10




FIGURE 11




Figure 12




Figure 13




Figure 14

PROGRAM		VBL (V)	VWL (V)	PROGRAM	
	SC/SR	V_{pp}	0	YES	401
	SC/UR	V_{pp}	Floating	NO	403
	UC/SR	< 0.5	0	NO	405
	UC/UR	< 0.5	Floating	NO	407
				ISENSE	
READ	SC/SR	V_{DD} or V_{CC}	0	YES	409
	SC/UR	V_{DD} or V_{CC}	V_{DD} or V_{CC}	NO	411
	UC/SR	0 or Float	0	NO	413
	UC/UR	0 or Float	V_{DD} or V_{CC}	NO	415

FIGURE 15

Fig 16





Fig 17

0.18um/0.13um XPM CX cell operation

		Vbl (V)	Vwl (V)	Program
Program	SB/SW	Vpp	0	Yes
	SB/UW	Vpp	PC to Vpp/2 and FL	No
	UB/SW	<0.5v	0	No
	UB/UW	<0.5v	PC to Vpp/2 and FL	No
				Isense
Read	SB/SW	Vdd or Vcc	0	Yes
	SB/UW	Vdd or Vcc	Vdd or Vcc	No
	UB/SW	0	0	No
	UB/UW	0	Vdd or Vcc	No

Vpp = 8~9V for Gox=32A (0.18um) or 5-7 for Gox=20A, or 3~4.5 V for 10-15A (5 to 10A thinner than normal-standard Gate oxide).

Vdd = I/O Voltage 3.3V or 2.5V

Vcc=1.8V for 0.18um and 1.2V for 0.13um

Fig 18




Fig 19

Step 1:




Fig 20




Fig 21




Fig 22




Fig 23




Fig. 24




Fig 25




Fig 26




Fig 27




Fig 28

XPM P+Poly/BN+ 1T cell operation

		Vbl (V)(P+poly)	Vwl (V) (BN+ Diffusion)	Program
Program	SC/SR	Vbp	Vwp	Yes
	SC/UR	Vbp	Floating	No
	UC/SR	<0.5V	Vwp	No
	UC/UR	<0.5V	Floating	No
				Isense
Read	SC/SR	Vrd	0	Yes
	SC/UR	Vrd	Vrd	No
	UC/SR	0	0	No
	UC/UR	0	Vrd	No

Fig 29




Fig 28A




Fig 30




Fig 31

XPM N+poly/BP+ 1T cell operation

		Vbl (V)(N+poly)	Vwl (V)(BP+)	N-	Program
Program	SC/SR	Vbp	Vwp	Vwp	Yes
	SC/UR	Vbp	Floatin	Vwp	No
	UC/SR	(0 ~ -	Vwp	Vwp	No
	UC/UR	(0 ~ -	Floatin	Vwp	No
					Isense
Read	SC/SR	0	Vrd	Vdd or Vrd	Yes
	SC/UR	0	0	Vdd or Vrd	No
	UC/SR	Vrd	Vrd	Vdd or Vrd	No
	UC/UR	Vrd	0	Vdd or Vrd	No

Fig 32




Figure 33